

Product Code: GM2046GYSS

Luckinslive 425338865

Description: 20AX Double Pole Keyswitch Module



General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 22.5 (D)		
Finish	Stainless Steel		
Insert Colour	Grey		
Materials	Body & Insert: Nylon		Switch: Nylon
	Insert Cover: Stainless Steel		Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated		Contacts: Silver "on-lay" Copper / Brass
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Inductive Load Rating (AX)	20		
Load Rating Comments	Suitable for Fluorescent or Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4		
Double Pole Switch	Yes		
Keyswitch	Yes		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,

Tamworth, Staffordshire, B79 7UL United Kingdom

T: +44 (0)1827 63454 | F: +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com



Catalogue



Range



DoC



Installation

