

Technical Specification

Product Code: GM2075PWSC
 Description: 20AX 3 Position Centre 'Off' Retractive Switch Module



General Information

Dimensions	24.5mm (W) x 50mm (H) x 26mm (D)
Aperture Dimensions	20mm (W) x 35mm (H)
Module Frame Finish	Satin Chrome
Switch Finish	Satin Chrome
Materials	Body & Insert: Nylon Switch: Urea Switch Cover: Stainless Steel Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Springs: Spring Steel
Maximum Voltage	250V 50Hz
Load Rating	20AX (Suitable For Inductive Loads)
Terminal Size	5mmø
Termination Type	Screw
Terminal Torque	1.2Nm
Terminal Capacity	3 x 2.5mm ² or 1 x 4mm ²
Switch Contact	Press to Make
Back Box Depth	Dependent On Plate Used
Operational Temperature	-5°C to +40°C
Warranty	10 Years

Standards
 BS EN 60669-1:2018

Additional Information
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Design Registration: 3015621