






collingwood

01604 495 151
collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

Springbok Lite 11,000lm

80W High bay luminaire (Replaces 150W or 2x80W T5)

Features

IK rating	IK08
IP rating	IP65
Sensor	Microwave & Daylight
Dimmable Option	No
Input	220-240V 50/60Hz Surge protection 6KV
LED Lifetime	54,000h L70
CRI	80 Ra
SDCM	5 SDCM
Emergency version available	Yes

Installation information

Install Connector Type	Flying lead
Construction Material	ADC12 aluminium alloy tempered glass
Weight	1.60
Maximum ambient temperature	-20 to +40
Building regulations	Part P
Electric Class (1, 2, 3)	1

Guarantee

4 years, 2 years on battery, 2 years on-site

Features & benefits

Economical high bay for fast return on investment

Easy to add microwave sensor kit includes junction box and counter weight

On/off control with time delay and daylight switching (8-15 metres max)

Suitable for jack chain, M10 drop rod or catenary wire suspension

Pre-wired with 1.5M of H05RN-F cable for ease and speed of installation

Replaceable driver for easy maintenance

IK08 for robust impact protection

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m	EM
HBLIN	Matt black RAL9017	80W	4000K	110°	11000	138	3968	530
HBLINEM	Matt black RAL9017	80W	4000K	110°	11000	138	3968	530

Wiring information

Cable / Flying Lead	1.5m H05RN-F 3x1.0mm ² Ø7mm
Type of Wiring Required	Parallel

Accessories

HBLMWS	High Bay Sbok Lite, Microwave sensor kit inc junction box and counterweight	Sold Separately
HBREM	High Bay Sbok Lite, Remote control for commissioning HBLMWS	Sold Separately
HBLIREFR	High Bay Sbok Lite, 80W 80-degree refractor	Sold Separately

Beam angle: 110°

