

Open plan area (continued)

Primary lighting



Area Bay remote

Remote for sensor control

Compatible with Area Bay & Springbok Lite

Code: HBREM



Bracket

Bracket Mount for Standard High Bay

Compatible with Area Bay

Code: HBBRA



Bracket

Extended Bracket Mount Reduces mounting height by 265mm

Compatible with Area Bay

Code: HBBRAEXT



M20 Rod Mount Kit

Reduces mounting height by 1.5 metres

Compatible with Area Bay

Code: HBROD



Lentus 100W

120° linear light



Code: LB10040
100W | 15,000lm | 4000K

Code: LBAL5090
50x90° lens for rectangular distribution



Lentus 150W

120° linear light



Code: LB15040
150W | 22,000lm | 4000K

Code: LBAL5090
50x90° lens for rectangular distribution



Borealis 5ft single

Quick to install



Code: BT5SS40
32W | 4160lm | 4000K



Open plan area (continued)

Primary lighting



Borealis 5ft twin

Quick to install



Code: BT5SS40
54W | 7020lm | 4000K



Borealis 6ft single

Quick to install



Code: BT6SS40
42W | 5200lm | 4000K



Borealis 6ft twin

Quick to install



Code: BT6TS40
70W | 8680lm | 4000K



PIR bolt

Bolt-on accessory
PIR + Daylight Switch
Use up to 6 metres
Take 4 minutes to fit

Compatible with Borealis & Lentus



Racking aisle

Primary lighting



Springbok Lite 200W

Replaces 400W or 4x80W T5



Code: HBL3N
200W | 27,000lm | 4000K

Code: HBL3NEM
Emergency variant, manual Test



Low glare refractor

Boosts light by 20%, <UGR22

Code: HBL3REFR
Polycarbonate Prismatic
80-degree beam angle
Can be retro-fitted on site

