

Datasheet

Helvellyn 2.0



Product Description

This sleek, stainless steel LED bollard has an on site adjustable output for optimum performance.


Specification Text

The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 124 lm/W and will be capable of producing up to 1,860 luminaire lumens at 4000K with a CRI >70. It shall have a radial distribution and is rated at IP65 and IK08.

Specification

Weight: 10.3kg
Material: Die-cast Aluminium
Paint finish: Stainless Steel Finish

Optics



Radial

Key Features

- 7.5 - 15W
- 930 - 1,860 Luminaire Lumens
- Efficacy up to 124lm/W
- 4000K, CRI >70
- Lifetime >50,000hr, L70



Mounting Options

- Flange Mount
[Contact for details](#)

Other Options

- Colour Temperature Options
- Photocell Option
[Contact for details](#)

Code	Power	Luminaire Lumens	Drive Current	Optic	CCT(K)	IP	IK	Weight kg	Paint Finish	Driver Included	Driver Type
HEL715	7.5/15	930/1,860	250/500	Radial	4000	IP65	IK08	10.3	Stainless Steel	Driver Inc	Fixed
HEL715EM	7.5/15	930/1860	250/500		4000	IP65	IK08	10.3	Stainless Steel	Driver Inc	Fixed



Dimensions

