


JC1102/BN

X50

X50 Fire rated Tilt downlight 3W/5W IP65 3000/4000/5700K 400/650 lms
Brushed nickel

Features & Benefits

- Two wattage and three colour selectable from remote driver
- Two-part first fix connector with dedicated testing terminals
- Double hinged terminal for easy access to terminal blocks
- Tested for use in Solid, I-Joist and Steel Open Web joist ceilings
- 20° tiltable adjustment
- Triac dimmable as standard, see JCC.co.uk for approved dimmer list



General Information

Mounting	Recessed
Environment	Demanding
Suitable For Zones	Zone 1
Product Group	Fire-rated Downlights
Color Finish	Brushed nickel
Product Shape	Round
Product Range	X50
Overall Dimensions	100Ø x 58.4 x 547 cm (sse profile drawing for details)
Length (mm)	547
Height (mm)	58.4
Diameter (mm)	100
Product Weight(kg)	0.390
Light Source	LED
Light Source Features	3CCT Switchable
Additional Information	For Emergency version, use JC131003 only. Not suitable for use with JCEM002/JCEM002ST

Recommended product location	Indoor use only
Minimum Void Requirement	50mm
Method of fix	Spring clips
Distance from lighted object	0.3m
Product Aperture Size	83mm Ø
Max Angle Of Tilt & Rotation	20° Tilt only
IP Rating	IP65
	Tested for use in fire-rated ceilings. Full information and upto-date fire testing certificates for ceiling system types are available on JCC.CO.UK
	China
	5 Year Warranty(Terms & conditions apply)
	Triac dimmable
	JCC
	Downlight
	Fire-rated

Electrical

Voltage Rating	230-240
Primary Running Current(Amp)	0.0018/0.0026
Operating Frequency Hz	50/60
Secondary running current(mA)	0.0083/0.0127
Constant Current or Constant Voltage	CC
Luminaire Circuit Wattage	3/5 selectable
Class	II
Output Voltage Max/Range (VDC)	33
EMC Compliant (EN55015)	Yes
Input Electrical Connections	Live, Earth, Neutral
Dimmable	Yes, Triac dimmable only

Thermals

Thermal Cut Out	Yes
Insulation Coverage	Loosely Cover with Mineral Wool Insulation
Minimum Void Requirement	50mm
Operating Temperature Range °C	0 to 26

Performance Data

Energy Rating	This product contains a light source of energy efficiency class A
Actual Lumen Output	480/700
Lumens Per Circuit Watt	137/140
Color Rendering Index	80-89
CRI: Ra	80
Correlated Color Temperature	3000/4000/5700K
Beam Angle °	60°

LOR (Light Output Ratio) %
Photometry Available

100
Yes

Construction

Driver Housing

Polycarbonate

Packaging

Product Bar Code EAN-13 Number

5052544121661

Standards & Approvals

Manufactured in accordance to
CE Marked
UKCA Marked
Date code/Purchase order No.
WEEE symbol
Certificate Of Conformity
Accredited Members

BS EN 60598:2015, 2-1, 2-2
Yes
Yes
Yes
Yes
available on request
LIA, ISO9001-2015, ISO14001-2015

