



## DATASHEET



### LANT2

### 230V IP54 LED Wall Lantern with PIR

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



| MLA PART CODE                 | LANT2   |
|-------------------------------|---|
| DESCRIPTION                   | 230V IP54 LED Wall Lantern with PIR   |
| NET WEIGHT (KG)               | 0.57  |
| FINISH                        | Black   |
| DIFFUSER                      | Opal  |
| DIMENSIONS (MM)               | Height - 375<br>Width - 177<br>Projection - 230<br>Base Diameter - 97<br>Base Width - 113<br>Base Height - 143<br>Base Depth - 26 |
| CONSTRUCTION                  | Construction - Polycarbonate  |
| CLASS                         | II  |
| IP RATING                     | IP54  |
| WATTAGE (W)                   | 8   |
| LAMP TECHNOLOGY               | LED   |
| LAMP INCLUDED                 | Yes   |
| LUMENS (LM)                   | 555   |
| LUMENS LIGHT SOURCE ONLY (LM) | 1085  |
| LUMEN TOLERANCE               | 5%  |
| EFFICACY (LM/W)               | 137.6   |
| CIRCUIT WATTAGE (W)           | 7.9   |
| CCT                           | 4000K   |
| LIGHT COLOUR                  | Cool White  |
| CRI                           | >85   |
| SDCM                          | <6  |
| RUNNING CURRENT (A)           | 0.067   |
| DISPLACEMENT FACTOR           | >0.7  |
| SVM                           | 0.001   |
| PST-LM                        | 0.041   |

|  |                             |
|--|-----------------------------|
| BEAM ANGLE (DEGREES)                     | 315                         |
| LIFE SPAN (HRS)                          | 30,000                      |
| L70B50 LIFESPAN (HRS)                    | 60,000                      |
| DIMMABLE                                 | No                          |
| OPERATING TEMPERATURE                    | -20~50°C                    |
| INPUT VOLTAGE                            | 230V 50Hz                   |
| CABLE GLAND INCLUDED                     | Blind grommet               |
| DRIVER                                   | EFFICIENCY FULL LOAD - 85   |
| SENSOR TYPE                              | PIR                         |
| SENSOR OVERRIDE                          | Yes                         |
| SENSOR DETECTION ANGLE (DEGREES)         | 90                          |
| OPTIMUM DETECTION RANGE (M)              | 8                           |
| SENSOR DURATION                          | 60 seconds (non-adjustable) |
| SENSOR LUX SETTINGS                      | <15 lux (non-adjustable)    |
| STANDBY POWER                            | 0.42W                       |
| WARRANTY                                 | 3year(s)                    |
| MANUFACTURED IN ACCORDANCE WITH          | BS EN 60598                 |
| ORIGIN OF MANUFACTURE                    | China                       |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes                         |
| EAN                                      | 5055832947936               |

Date Created: 08/01/2024 13:30

