

EMERGENCY LUMINARIES SPECIFICATION SHEET



LEDEP10

Emergency converter, Self-test.

FEATURES

IP rating	IP20
Input	220-240V 50-60Hz

INSTALLATION INFORMATION

Install Connector Type	Mains: Push-fit terminals 0,5 - 2,5mm ² DC: Plug & Play connectors
Insulation Coverable	No
Double Insulation	Yes
Cut Out Size	Ø18mm (status LED) Ø7mm (test button)
Inrush Current	10A
Construction Material	Polycarbonate
Weight	390g
Case Temperature (tc = °C)	60°C
Maximum ambient temperature	0 - 45°C
SELV	Yes
Electric Class (1, 2, 3)	2

ACCESSORIES

No accessories required

PRODUCT CODES

Product code	Finish	Description	Wattage	Feature I	Feature II
LEDEP10	White matt	Emergency converter, Self-test.	2.5W	LiFePO4 battery	6.4V 1500mAh



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

@collingwoodLED

/collingwoodlighting

collingwoodled

GUARANTEE / WARRANTY

3 year extended guarantee

FEATURES & BENEFITS

Self-test device, simplifying the emergency lighting inspections

Dual colour Green / Red LED status indicator

A minimum of 3 hours of emergency lighting

Built-in protection:

- open circuit
- over charging
- over discharging
- over temperature

LiFePO4, provides long operational life

Supplied with a test button, whereby a battery duration test can be carried out at anytime

Synchronizes an automatic battery duration test every 6 months

Compatible with our Solis panels, Thea commercial downlights, H2 Pro, 1901 and H5 downlights, however this does not apply to trimless