

Datasheet

Guardian Pro



Product Description

This asymmetric flood light offers a powerful fixed output in a small package. It also comes with an adjustable bracket in order to get the perfect illumination for your scheme.

Specification Text


The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 130.0 lm/W and will be capable of producing up to 26,000 luminaire lumens at 4000K with a CRI >70. It shall have an asymmetric optic and is rated at IP65 and IK07.

Specification


Weight: 4.7 - 9.3kg
 Material: Die-cast Aluminium
 Paint finish: RAL7016 Anthracite Grey Finish

Key Features

- 50.0 - 200.0W
- 6,800 - 26,000 Luminaire Lumens
- Efficacy up to 130.0 lm/W
- 4000K, CRI >70
- Lifetime > 70,000hr, L80



Optics



Asymmetrical Flood

Code	Power	Luminaire Lumens	Optic	CCT(K)	IP	IK	Weight kg	Paint Finish	Driver Included
LFP50B140F	50.0	6,800	Asymmetrical Flood	4000	IP65	IK07	4.7	RAL7016 Anthracite Grey	Driver Inc
LFP100B140F	100.0	12,500		4000	IP65	IK07	7.4	RAL7016 Anthracite Grey	Driver Inc
LFP150B140F	150.0	19,200		4000	IP65	IK07	7.4	RAL7016 Anthracite Grey	Driver Inc
LFP200B140F	200.0	26,000		4000	IP65	IK07	9.3	RAL7016 Anthracite Grey	Driver Inc



Dimensions

