

Technical Specification

CLICK® Scolmoregroup

Product Code: MD004WH Description: 10AX 2 Way Retractive Switch Module





General Information

Dimensions 25mm (W) x 53mm (H) x 20mm (D)

Aperture Dimensions 16mm (W) x 31.5mm (H)

Finish Click White

Materials Rocker Switch: Urea

Rear Housing: Nylon Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Maximum Voltage 250V 50Hz

Load Rating 10AX (Suitable For Inductive Loads)

Terminal Size 3.5mmø
Terminal Torque 0.4Nm

Terminal Capacity 4 x 1.5mm² or 2 x 2.5mm²
Switch Contact Press to Make or Break
Back Box Depth Dependent On Plate Used

Operational Temperature -5°C to +40°C
Warranty 10 Years

wallality 10 lears

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches both the Deco white range and Metal Clad range.