



## **Technical Specification**

| Product Coc | СН |
|-------------|----|
| FIUUUCI COU | ОП |



## Description: 10AX Ingot 1 Way Retractive Switch Module



## **General Information**

| Dimensions              | 25mm (W) x 53mm (H) x 20mm (D)   |
|-------------------------|--|
| Aperture Dimensions     | 16mm (W) x 31.5mm (H)  |
| Finish                  | Polished Chrome  |
| Materials               | Rocker Switch: Urea<br>Rear Housing: Nylon<br>Switch Cover: Stainless Steel<br>Terminals: Brass<br>Terminal Screws: Steel & Yellow Passivated<br>Contacts: Silver "on-lay" Copper / Brass<br>Internal Busbars: Formed Pressed Brass        |
| Maximum Voltage         | 250V 50Hz  |
| Load Rating             | 10AX (Suitable For Inductive Loads)  |
| Terminal Size           | 3.5mmø   |
| Terminal Torque         | 0.4Nm  |
| Terminal Capacity       | 4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>   |
| Switch Contact          | Press to Make  |
| Product Markings        | Bell Symbol  |
| Back Box Depth          | Dependent On Plate Used  |
| Operational Temperature | -5°C to +40°C  |
| Warranty                | 10 Years   |
| Standards               | BS EN 60669-1:1999 +A1:2002 +A2:2008   |
| Additional Information  | Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.<br>Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. |