

# Technical Specification

Product Code: MD047PW

Description: 13A Fused Connection Module



## General Information

<b>Dimensions</b>	25mm (W) x 57mm (H) x 25.2mm (D)
<b>Aperture Dimensions</b>	16mm (W) x 31.5mm (H)
<b>Finish</b>	Polar White
<b>Frame</b>	Polar White
<b>Materials</b>	Cover & Fuse Drawer: Nylon Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass
<b>Maximum Voltage</b>	250V 50Hz
<b>Load Rating</b>	13A
<b>Terminal Size</b>	3.5mm $\varnothing$
<b>Terminal Torque</b>	0.4Nm
<b>Terminal Capacity</b>	4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>
<b>Product Markings</b>	Fused Symbol
<b>Fuse Fitted</b>	13A (BS 1362)
<b>Back Box Depth</b>	Dependent On Plate Used
<b>Operational Temperature</b>	-5°C to +40°C
<b>Warranty</b>	10 Years
<b>Standards</b>	BS 5733: 2010

## Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
Suitable and matches the Definity, Mode, Polar & Part M ranges