

Inline Shower Fan Range

Designed for the safe ventilation of bathrooms, toilets and shower rooms by removing any risk of an electric shock in wet areas as the fan is mounted remotely.

| Cat No. | Product Type |
|---------|---|
| LSF100T | 100mm Timer model incorporating integral adjustable electronic timer (1-20 mins). Also comes with 1.5m PVC ducting, grille fixing clips, cable ties, screw plugs as well as both internal and external grilles. |
| LSF150T | 150mm Timer model incorporating integral adjustable electronic timer (1-20 mins). Also comes with 3m PVC ducting, grille fixing clips, cable ties, screw plugs as well as both internal and external grilles. |

Additional Information

| Size: | Maximum Pressure Pa: | Fan Speed r.p.m.: | Sound Volume dB(A): | Maximum Operating Temperature °C: | Maximum Airflow l/s: | Power Consumption Watts: |
|------------|----------------------|-------------------|---------------------|-----------------------------------|----------------------|--------------------------|
| 4" (100mm) | 20 | 2400 | 41 | 40 | 24 | 10.4 |
| 6" (150mm) | 50 | 2400 | 40 | 40 | 63 | 20.2 |



SFP Down To
0.43 4" (100mm)
0.31 6" (150mm)

Showerlite Fan Range

The Manrose Showerlite is a distinctive Showerlite which is incorporated into a circular diffuser, suitable for showers and bathrooms. The Showerlite can be used within the splash area of the shower or bath and is powered by a S.E.L.V. remote safety isolating transformer.

| Cat No. | Product Type |
|----------|--|
| LSLKTC | 100mm Showerlite fan kit, complete with a adjustable over run timer (1-20mins) with chrome/white fitting showerlite and 12 volt transformer. Also comes with 1.5m PVC ducting, butterfly clips, cable ties, screw plugs as well as both internal and external grilles. |
| LSL150TC | 150mm Showerlite fan kit, complete with a adjustable over run timer (1-20mins) with chrome/white fitting showerlite and 12volt transformer. Also comes with 3m PVC ducting, butterfly clips, cable ties ,screw plugs as well as both internal and external grilles. |

Additional Information

| Size: | Maximum Pressure Pa: | Fan Speed r.p.m.: | Sound Volume dB(A): | Maximum Operating Temperature °C: | Maximum Airflow l/s: | Power Consumption Watts: |
|------------|----------------------|-------------------|---------------------|-----------------------------------|----------------------|--------------------------|
| 4" (100mm) | 20 | 2400 | 41 | 40 | 24 | 10.4 |
| 6" (150mm) | 50 | 2400 | 40 | 40 | 63 | 20.2 |



SFP Down To
0.43 4" (100mm)
0.31 6" (150mm)

Mixflo Range

These powerful 2 speed in-duct mounted mixed flow fans have been designed to produce higher working pressures for applications that require high air flows, with low relative noise. The Mixflo fans can be mounted in a variety of applications as shown and are suitable for use with either rigid or flexible ducting.

| Cat No. | Product Type |
|---------|--|
| MF100S | 100mm Standard model for remote switching |
| MF100T | 100mm Timer model incorporating integral adjustable electronic timer (1-20 mins) |

Additional Information

| Speed: | Maximum Pressure Pa: | Fan Speed r.p.m.: | Maximum Operating Temperature °C: | Maximum Airflow l/s (m³/hr): | Power Consumption Watts: |
|--------|----------------------|-------------------|-----------------------------------|------------------------------|--------------------------|
| Low | 180 | 1700 | 40 | 50 (180) | 20 |
| High | 200 | 2400 | 40 | 68 (244.8) | 25 |



SFP Down To
0.4 Low speed
0.37 High speed

