MLSA360NP

Multiway Mounting PIR Light Controller

Features & Benefits

- 200° detection angle / 12 meters frontal detection coverage.
- 360° Anti-creep detection Ø 5 meters at 2.5m mounting height.
- Sensor head adjustable by 90° horizontally and 30° downward.
- Multiple mounting options surface, ceiling, inner and outer corner mounting.
- Manual override function.
- Easy installation with 'Fast-fix Terminal Block' connection.
- Pulse function supports staircase timer operation.
- IP55 Ingress protection rating.
- Sensitivity adjustment for the detection area.



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	-20°C to 45°C
Ingress Protection Rating	IP55
Setting Type	Dial
Approved Mounting Height (m)	2.5
Motion Detection (m)	12 Frontal, 5m Downward
Detection Angle	200° Frontal, 360° Downward



Yes
Auto, Pulse, Test, Dusk To Dawn, Learn (Teach)
Yes
44
<0.5W
1
2000W High Voltage Halogen, 1000W Low Voltage Halogen, 1000VA / 900W Fluorescent, 900VA / 100uF Energy Saving, 600VA / 400W LED Lighting, 10A at 230V AC
1 to 20 Minutes
10 to 1000
200° Frontal 12m at 2.5m height. 360° Downward Ø5m at 2.5m
Yes (Pulse Override)
Yes
Yes
Back Entry, Bottom Entry (Knockouts)

General

Weight (g)	219
Height (mm)	74
Width (mm)	72
Depth (mm)	134
Body Construction	Polycarbonate
Product Colour	Black
Accessories (Included)	Rawl Plugs, Screws, Lens Mask
EAN Number	5012483016084
Guarantee Period	3 Years



Data sheet MLSA360NP

Light / PIR Lighting Controllers

Trade Tariff Commodity Code	8536508090
-----------------------------	------------

Line Diagrams



