

Product Code: MM002WH

Description: 10AX 2 Way Switch Module



**General Information**

<b>Dimensions</b>	25mm (W) x 50mm (H) x 22mm (D)
<b>Module Finish</b>	Polar White
<b>Materials</b>	Cover & Housing: Polycarbonate Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass
<b>Maximum Voltage</b>	250V~ 50Hz
<b>Load Rating</b>	10AX (Suitable for Inductive Loads)
<b>Terminal Size</b>	5mmø
<b>Terminal Torque</b>	1.8Nm
<b>Terminal Capacity</b>	4 x 1.5mm <sup>2</sup> or 3 x 2.5mm <sup>2</sup>
<b>Ingress Protection</b>	IP20
<b>Back Box Depth</b>	Dependent on Plate Used
<b>Termination Type</b>	Screw
<b>Operational Temperature</b>	-5°C to +40°C
<b>Warranty</b>	1 Year
<b>Standards</b>	BS EN 60669-1:1999 +A1:2002 +A2:2008

**Additional Information**

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.