Electrical performance:

CEI EN 50393 as applicable (testing under water head of the accessory installed in a box)

Gel: UL 94-HB



Operating temperature 90°



Installation temperature: -40°C / +50°C



Can be used underground





Ray New \ano Joint

Pre-filled gel accessories to seal, protect and make safe electrical connections. Inclusive of connectors

- Ready to use, quick, re-enterable!
- No tools required
- Can energise immediately
- For straight & branch connections
- For rigid or flexible insulated wires from 1 a 4 mm²
- For 1, 2 and 3 cores connections
- Up to 5 conductors on one phase or up to 2 conductors on two or three phase
- Small, compact and resistant





NANO LINE

Nano 3

	Formation and wires cross section		Pieces for	$A \times B \times C$
Product	(Max N° x mm²)	Combination	package	(mm)
Nano 3	3 x 1 - 4	2 through / 1 branch	4 pcs Blister	30 x 27 x 23



With one connector included for each Nano Joint





max 3 wires max 4 mm²

Nano 5

	Formation and wires cross section		Pieces for	AxBxC
Product	(Max N° x mm²)	Combination	package	(mm)
Nano 5	5 x 1 - 4	2 through / 3 branch	2 pcs Blister	30 x 42 x 26



With one connecto included for each Nano Joint





Nano 6

	Formation and wires cross section		Pieces for	AxBxC
Product	(Max N° x mm²)	Combination	package	(mm)
Nano 6	6 x 1 - 4	3 through / In/Out	1 pcs Blister	33 x 52 x 26



With three connectors included for each Nano Joint



