



WiFi Socket Range Extender



Expand your WiFi coverage throughout your home

Designed to work with all wireless broadband routers and easy to install with one touch WPS, this includes a USB charging port and eradicates the need for plug in adaptors, keeping sockets free for use. Designed to fit a 25mm backbox, ideal for retrofit.

**FITS
25MM
BOX**

**SMART
USB
CONNECTIVITY**

**300
MBPS**

**2.4
GHz
SINGLE BAND**

**N300
Mbps**



Brushed Steel

Polished Chrome

Black Nickel

Antique Brass

Pearl Nickel

WiFi Extender Socket and USB Charger 1 x Outlet (2.1A)

- Extend your WiFi coverage through-out your home
- Works with all wireless broadband routers
- Easy to install and setup with one touch WPS
- N300 WiFi technology – Up to 300Mbps data transfer speed. Single band (2.4GHz)
- Perfect for streaming music and videos or playing online games
- USB charger ideal for phones, tablets, cameras and other USB devices
- Double switched socket with outboard rockers
- Minimum mounting box depth – 25mm; ideal for retrofit
- Manufactured to BS1363-2
- Terminal capacity 3x 2.5mm², 3x 4.0mm² & 2x 6.0mm²



NBN22UWRB

Brushed Steel	Polished Chrome	Black Nickel	Antique Brass	Pearl Nickel	Description
NBS22UWRW	NPC22UWRW	-	-	NPR22UWRW	Double, 13A, SP switched with WiFi extender + 1 x USB (2.1A), White insert
NBS22UWRG	-	-	-	-	Double, 13A, SP switched with WiFi extender + 1 x USB (2.1A), Grey insert
NBS22UWRB	-	NBN22UWRB	NAB22UWRB	-	Double, 13A, SP switched with WiFi extender + 1 x USB (2.1A), Black insert

13 Amp Switched Socket Outlets

- Manufactured to BS 1363 part 2
- Terminal capacity 3 x 2.5mm², 3 x 4.0mm² & 2 x 6.0mm²
- Minimum mounting box depth 25mm
- Twin earth fitted as standard to allow a double earth facility for installations requiring high integrity protective connection Ref. BS 7671:2008

*Brushed Steel insert colours = white (W), grey (G) and black (B) at the end of the product code



NBN22B

Brushed Steel	Polished Chrome	Black Nickel	Antique Brass	Brushed Iridium	Matt Black	Pearl Nickel	Description	Inner Carton	Outer Carton
NBS21W	NPC21W	-	-	-	-	-	Single, 13 Amp switched socket	5	50
NBS21B	-	NBN21B	NAB21B	NBI21B	NMB21B	NPR21W	Single, 13 Amp switched socket	5	50
NBS21G	-	-	-	-	-	-	Single, 13 Amp switched socket	5	50
NBS22W	NPC22W	-	-	-	-	NPR22W	Single, 13 Amp switched socket	5	50
NBS22B	-	NBN22B	NAB22B	NBI22B	NMB22B	-	Double, 13 Amp switched socket	5	50
NBS22G	-	-	-	-	-	-	Double, 13 Amp switched socket	5	50
NBS22DPOBB	-	-	-	-	-	-	Double, 13 Amp switched socket	5	50
NBS24W	-	-	-	-	-	-	Double, 13 Amp unswitched socket, outboard rockers	5	50

Combination Plate

- Twin earth fitted as standard
- Manufactured to BS 1363 part 2
- Terminal capacity 3 x 2.5mm², 3 x 4.0mm² & 2 x 6.0mm²
- Mounting box depth 47mm (HGS07/C4)
- Modules of mains and extra low voltage rating must not be fitted to the same front plate aperture Ref. BS 7671:2008



NBS222GEM8

Brushed Steel	Polished Chrome	Description	Inner Carton	Outer Carton
NBS222EM8W	NPC222EM8W	2 x Double socket + 2 x 4 Module aperture	5	50

- See our Euro Module range for further Telecom, Data and Co-axial Options

10 Amp 10AX Plate Switches

- Plate switches manufactured to BS EN 60669-1
- Terminal capacity 4 x 1.0mm², 4 x 1.5mm², 2 x 2.5mm² & 1 x 4.0mm²
- Captive terminal screws
- Minimum mounting box depth:
Single and Double – 16mm, Triple and Quadruple – 25mm

*Bell push switch made to order, contact Customer Services for more details



NAB43

NBS12

Brushed Steel	Polished Chrome	Black Nickel	Antique Brass	Brushed Iridium	Matt Black	Pearl Nickel	Description	Inner Carton	Outer Carton
NBS12	NPC12	NBN12	NAB12	NBI12	NMB12	NPR12	Single, 2 way	5	50
NBS13	NPC13	NBN13	NAB13	NBI12	NMB13	NPR13	Intermediate	5	50
NBS14	NPC14	-	-	-	-	-	Bell push **	5	50
NBS42	NPC42	NBN42	NAB42	NBI42	NMB42	NPR42	Double, 2 way	5	50
NBS43	NPC43	NBN43	NAB43	NBI43	NMB43	NPR43	Triple, 2 way	5	50
NBS44	NPC44	NBN44	-	-	-	-	Quadruple, 2 way	5	50
NBS46	-	-	-	-	-	-	Sextuple, 2 Way	5	50