m14









AquiP66°

IP66 Weatherproof Switched Sockets

OA035AG 13A 1 Gang DP IP66 Weatherproof Switched Socket Unit

Fitted with 1 gang Mode® switched socket

OA036AG 13A 2 Gang DP IP66 Weatherproof Switched Socket Unit

Fitted with a 2 gang Mode® switched socket

IP66 Weatherproof Socket Enclosures

OA501AG 1 Gang IP66 Weatherproof Unfurnished Unit OA502AG 2 Gang IP66 Weatherproof Unfurnished Unit

Accessory supplied separately. Accepts accessories up to 35mm deep

Standards: BS EN 60529 (Enclosure), BS 1363 (Socket) Knock-outs: 20mm (Socket) Cable Size: 4 x 2.5mm², 2 x 4mm² Dimensions: 1 Gang: From Front: 158mm (Height) x 100mm (Width) x 90mm (Depth - with Gasket)
From Rear: 130mm (Height) x 105mm (Width). 2 Gang: From Front: 158mm (Height) x 158mm (Width) x 90mm (Depth - with Gasket)
From Rear: 130mm (Height) x 165mm (Width) Back Box Depth: 35mm

Metal Clad Accessories

10AX Switches | Unfurnished Switch Plates 20A Switches | 13A Socket Outlets Fused Connection Units | 45A Switches Telephone & Coaxial Socket Outlets New Media™ Plates | Mounting Boxes & Blank Plates

A comprehensive selection of Metal Clad electrical accessory products are featured in the following pages. Electrophoretically coated plates and back boxes provide a durable and long lasting heavy duty finish to this attractive range of products.

All switch products are of modular construction allowing the installer total freedom in designing customised switching solutions according to on-site needs.

All socket outlets and spurs are tested and approved to BS1363. Unfurnished plates and mounting boxes are available for use in conjunction with our extensive range of Minigrid[™] and New Media[™] modules.

MINIGRID





of the catalogue are finished plates and

For comprehensive information on the full range of modules available please refer to our Minigrid[™] product brochure.

