

## 3 Pin Pre-wired 6A Plugs

### Characteristics:

- 6A pre-wired plugs are used to connect luminaires to a Klik ceiling rose or marshalling box. All leads have prepared ends.
- Complies with BS 6972 and BS 5733:2010.
- PVC flexible cord complies with BS EN 50525-2-11.
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11.

Description	Quantity	PVC Cat ref.	LSZH Cat ref.
<b>6A Pre-wired Plugs with 0.75mm<sup>2</sup> Flexible Cord</b>			
1 Metre	10	<b>P22/1.0</b>	<b>P22/LSF/1.0</b>
2 Metre	10	<b>P22/2.0</b>	<b>P22/LSF/2.0</b>
3 Metre	5	<b>P22/3.0</b>	<b>P22/LSF/3.0</b>
4 Metre	5	<b>P22/4.0</b>	<b>P22/LSF/4.0</b>



P22/1.0

### 6A Pre-wired Plugs with 1mm<sup>2</sup> Flexible Cord

2 Metre	10	<b>P22/1.0PVC/2</b>	<b>P22/1.0LSF/2</b>
3 Metre	5	<b>P22/1.0PVC/3</b>	<b>P22/1.0LSF/3</b>
4 Metre	5	<b>P22/1.0PVC/4</b>	<b>P22/1.0LSF/4</b>
5 Metre	5	<b>P22/1.0PVC/5</b>	<b>P22/1.0LSF/5</b>

## 4 Pin (Including Auxiliary) Pre-wired 6A Plugs - White

### Characteristics:

- Klik auxiliary 6A pre-wired plugs are used to connect luminaires to a Klik ceiling rose or marshalling box.
- Complies with BS 6972 and BS 5733:2010.
- PVC flexible cord complies with BS EN 50525-2-11.
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11.
- All leads have prepared ends.

Description	Quantity	PVC Cat ref.	LSZH Cat ref.
<b>6A Pre-wired Plugs with 0.75mm<sup>2</sup> Flexible Cord</b>			
1 Metre	10	<b>P64AX/1.0</b>	<b>P64AX/LSF/1.0</b>
2 Metre	10	<b>P64AX/2.0</b>	<b>P64AX/LSF/2.0</b>
3 Metre	5	<b>P64AX/3.0</b>	<b>P64AX/LSF/3.0</b>
4 Metre	5	<b>P64AX/4.0</b>	<b>P64AX/LSF/4.0</b>



P64AX/1.0

### 6A Pre-wired Plugs with 1mm<sup>2</sup> Flexible Cord

2 Metre	10	<b>P64AX/1.0PVC/2</b>	<b>P64AX/1.0LSF/2</b>
3 Metre	5	<b>P64AX/1.0PVC/3</b>	<b>P64AX/1.0LSF/3</b>
4 Metre	5	<b>P64AX/1.0PVC/4</b>	<b>P64AX/1.0LSF/4</b>
5 Metre	5	<b>P64AX/1.0PVC/5</b>	<b>P64AX/1.0LSF/5</b>

## 4 Pin (Including Auxiliary) Pre-wired 6A Plugs - Red

### Characteristics:

- Klik auxiliary 6A pre-wired plugs are used to connect luminaires to a Klik ceiling rose or marshalling box.
- Complies with BS 6972 and BS 5733:2010.
- PVC flexible cord complies with BS EN 50525-2-11.
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11.
- All leads have prepared ends.

Description	Quantity	PVC Cat ref.	LSZH Cat ref.
<b>6A Pre-wired Plugs with 0.75mm<sup>2</sup> Flexible Cord</b>			
1 Metre	10	<b>P64AXR/1.0</b>	<b>P64AXR/LSF/1.0</b>
2 Metre	10	<b>P64AXR/2.0</b>	<b>P64AXR/LSF/2.0</b>
3 Metre	5	<b>P64AXR/3.0</b>	<b>P64AXR/LSF/3.0</b>
4 Metre	5	<b>P64AXR/4.0</b>	<b>P64AXR/LSF/4.0</b>



P64AXR/1.0

### 6A Pre-wired Plugs with 1.00mm<sup>2</sup> Flexible Cord

2 Metre 1.00mm <sup>2</sup> Flexible Cord	10	<b>P64AXR/1.0PVC/2</b>	<b>P64AXR/1.0LSF/2</b>
3 Metre 1.00mm <sup>2</sup> Flexible Cord	5	<b>P64AXR/1.0PVC/3</b>	<b>P64AXR/1.0LSF/3</b>
4 Metre 1.00mm <sup>2</sup> Flexible Cord	5	<b>P64AXR/1.0PVC/4</b>	<b>P64AXR/1.0LSF/4</b>
5 Metre 1.00mm <sup>2</sup> Flexible Cord	5	<b>P64AXR/1.0PVC/5</b>	<b>P64AXR/1.0LSF/5</b>