

Panels

UGR 16 Low UGR with UGR16 available

DIM DALI-2, Push-Dim, & 0-10V options are available when using the plug-in PS6501100MA driver

EM Emergency option is available with LEDEP10

Guarantee	5 years (product), 3 years (emg battery)
Wattage	30W
IP rating	IP40
Dimmable	Yes (DALI 2, 0-10V, PUSH-DIM)
UGR	<16 <19 <22
TP rating	TP(a)
Input	220-240V 50/60Hz
Emergency version available	Yes, using converter. See accessories section.
Connector	2 part first fit connector
Electric class	2




Solis 600x600

4000K + 5000K Panel Range



2 year
on site
guarantee



Product code	W	UGR	Driver	Dimming	Colour	Beam	lm	lm/W
P2A16S30WA	30W	UGR16	Driver included	On-Off	4000K	90°	3450	115
P2A16X30WA	30W	UGR16	PS6501100MA or EUP30T-1HMC-0	DALI2/0-10V/Push-Dim	4000K	90°	3450	115
P2A19S40WA	40W	UGR19	Driver included	On-Off	4000K	90°	4600	115
P2A19X40WA	40W	UGR19	Driver excluded Use PS6501100MA	Dimmable	4000K	90°	4600	115
P2A22S30WA	34W	UGR22	Driver included	On-Off	4000K	110°	3400	100
P2A22S40WA	40W	UGR22	Driver included	On-Off	4000K	110°	4400	110
P5A19S30WA	30W	UGR19	Driver included	On-Off	5000K	90°	3450	115
P5A19X30WA	30W	UGR19	Driver excluded Use PS6501100MA	Dimmable	5000K	90°	3450	115

*Emergency packs sold separately

Product code	Description
LEDEP10EM	Emergency pack for converting panels into emergency manual-test option
LEDEP10	Emergency pack for converting panels into emergency self-test option
LEDEP09DA	Emergency pack for converting panel into DALI emergency self-test option