


DATASHEET



RE6CTT

RenuLED Tilt - 6W Fire-rated LED Downlight with 3 x CCT

www.mlaccessories.co.uk



MLA PART CODE	RE6CTT
DESCRIPTION	RenuLED Tilt - 6W Fire-rated LED Downlight with 3 x CCT
NET WEIGHT (KG)	0.163
FINISH	White
DIMENSIONS (MM)	Diameter - 86 Projection - 2 Overall Height - 64 Recessed Depth - 62 Minimum Void - 62
CUT-OUT (MM)	Cut-out Diameter - 55-70
TILT (DEGREES)	20
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	6
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	560/630/590
LUMENS LIGHT SOURCE ONLY (LM)	665
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	115.3
CIRCUIT WATTAGE (W)	5.76
CCT	3000/4000/6500K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.02944
DISPLACEMENT FACTOR	>0.7
SVM	0.001
PST-LM	0.013

BEAM ANGLE (DEGREES)	50
LIFE SPAN (HRS)	30,000
DIMMABLE	Yes*
FIRE-RATED	Tested to 30/60/90 minutes
I-JOIST RATED	30 minutes
WEB-JOIST RATED	30 minutes
IC RATED	Yes
OPERATING TEMPERATURE	25°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.15
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270853124

Date Created: 13/11/2024 13:22

