

## SAFE-D30/100

### Safe-D U-Clip 30 (Pack of 100)

Safe-D U-Clip 30 can be fitted direct-to-surface, or in size 2 (25mm or 30mm base) non-metallic trunking systems.

Ideally use with D-Fixing screws, then simply fold-over tabs to secure cables.

After cables are inserted, tabs can be folded inwardly to safely secure the cables.

The combination of the pliable gauge steel & rounded corner features makes Safe-D U-Clips quick & easy to install.



## Technical Specification

Production Method	Pressed
#1	Certified for 2 hours at 970°C
Material	Mild Steel
#2	Compliant with BS7671 and BS5839-1 requirements
Available Colours	Metallic & Red
#3	Thumb friendly, easy fold side-tabs
UV Stabilised	Yes
#4	Ideal for direct-to-surface, or popular PVC trunking
Operating Temperature	<970°C upto 2 hours
#5	Rounded edges for easy handling, & pliable gauge
Dimensions	(L) 20mm x (W) 23mm x (H) 8mm (folded - max height)
#6	Supplied in bags of 100 pcs
Length (mm)	20
#7	Made in UK
Width (mm)	23
Height (mm)	8
Paintable	Yes
Quality Approvals	BS 5839-1:2007
Design	Fix, insert cables fold to secure
Recyclability	Yes
Popular Usage	Secure cables direct-to-surface or in 25mm base PVC trunkings

