

Product Code: SCONTDC300W

Description: Acrylic Decorators Caulk (C3) Cartridge - White



Benefits

- Paintable with water based and synthetic paints
- Perfect adhesion without primer on most surfaces
- Almost odourless
- Easy to apply
- Easy to clean
- Non corrosive towards metals

A water based one component flexible caulk acrylic that is easy to apply, dries quickly and can be over painted with most emulsion and oil based paints.

Colour: White

Applications

Sealing and filling of interior gaps and cracks where movement can occur, such as those between skirting boards, ceilings, architraves, plasterwork, window and door frames. Use prior to painting or papering to prevent unsightly cracks developing later.

Directions Of Use

Cut the cartridge seal and screw on the nozzle which should be cut to your required size. Using a skeleton gun, apply the sealant into the gap or joint ensuring a good solid fill.

Limitations

- Not suitable for continuous exposure to water
- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

Paintability

Can be over painted with most emulsion and oil based paints when cured. For optimum results allow 24 hours drying before painting. Use product prior to painting or papering to prevent unsightly cracks developing later. Painting over with highly filled emulsion paint can cause cracks in the paint surface.

Cleaning

Tools to be cleaned after use with water. Hands can be cleaned with SX Multi-Purpose Cleaning Wipes and/or water and soap.

Additional Information


Application rate	@ Ø3 mm/4 bar	2200 g/min
Application temperature		+5°C to +40°C
Base		Acrylic dispersion
Density	ISO 1183-1	1,56 g/ml
Elongation at break	DIN 53505/ ISO 868	200%
Flow	ISO 7390	<2mm
Frost resistance during transportation		Down to -15°C
Shorea hardness	DIN 53505 / ISO 868	53
Skin formation	DBTM 16	7 minutes @ +23°C/50% RH
Temperature resistance		-20°C to +75°C
Tensile Strength	DIN 53504	0,52 N/mm²

These values are typical properties and may vary +/-3%

Shelf Life

In unopened original packaging between + 5°C and + 25°C, shelf life till 18 months after production date, stored in a dry place.

Certification

	EN 15651-1 F-EXT-INT
---	----------------------

Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request.