


Product Code: SFBZ157BK

Description: Isolated Satellite & Isolated Coaxial Outlet



### General Information

|                                        |                                                         |                                           |
|----------------------------------------|---------------------------------------------------------|-------------------------------------------|
| Insert Dimensions (mm)                 | 82.5 (W) x 82.5 (H) x 2.5 (D)                           |                                           |
| Plate Dimensions (mm)                  | 86 (W) x 86 (H) x 4 (D)                                 |                                           |
| Plate Fixing Centres - Horizontal (mm) | 60.3                                                    |                                           |
| Style                                  | Screwless Complete                                      |                                           |
| Finish                                 | Matt Bronze                                             |                                           |
| Insert Colour                          | Black                                                   |                                           |
| Compatible Cover Plate                 | SCP232#                                                 |                                           |
| Materials                              | Cover Plate: Stainless Steel<br>Earth Plate: Mild Steel | Insert: Polycarbonate<br>Terminals: Brass |
| Anti Microbial Certified               | No                                                      |                                           |
| Termination Type                       | Screw                                                   |                                           |
| Isolated                               | Yes                                                     |                                           |
| Isolated Comments                      | Enables 1 way signal, reducing signal interference      |                                           |
| Non-Isolated                           | No                                                      |                                           |
| Shielded                               | No                                                      |                                           |
| Minimum Back Box Depth (mm)            | 25                                                      |                                           |
| Ingress Protection                     | IP20                                                    |                                           |
| Operational Temperature (°C)           | -5 to +40                                               |                                           |
| Warranty (Years)                       | 20                                                      | Warranty - Electronics (Years) 2          |

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

