

Technical Specification

Product Code: SFBZ550BK

Description: 13A Ingot Fused Connection Unit With Optional Flex Outlet







General Information

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Dimensions (mm) 86 (W) x 86 (H) x 4 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Screwless Complete

Finish Matt Bronze

Insert Colour Black

Compatible Cover Plate SCP150#

> Materials Cover Plate: Stainless Steel Insert: Polycarbonate

> > Rear Housing: Urea Fuse Drawer Cover: Stainless Steel

Terminals: Brass Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel

Anti Microbial Certified

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13

> Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm) Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched

Twin Earth Terminals Product Marking Fused Flex Outlet Available Yes

Flex Outlet Location Front of Plate

Flex Outlet Dimension (mm) Ø10

Minimum Back Box Depth (mm) 35 Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









