

## **Technical Specification**

Product Code: SFBZ551BK

Description: 13A Ingot Double Pole Switched Fused Connection Unit With Optional Flex Outlet





## **General Information**

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Dimensions (mm) 86 (W) x 86 (H) x 4 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Screwless Complete

Finish Matt Bronze

Insert Colour Black

Compatible Cover Plate SCP151#

Materials Cover Plate: Stainless Steel Insert: Polycarbonate

> Rear Housing: Urea Switch & Fuse Drawer Cover: Stainless Steel Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Anti Microbial Certified

Frequency (Hz) 50 Operating Voltage (AC) 250

Resistive Load Rating (A) 13

> Fuse Fitted Type Plug Top Cartridge Fuse

**Termination Type** Screw

Terminal Size (mm) Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Switched Yes

Double Pole Switch Twin Earth Terminals Product Marking Fused Flex Outlet Available Yes

Flex Outlet Location Front of Plate

Flex Outlet Dimension (mm) Ø10

Minimum Back Box Depth (mm) 35 Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 1363-4, BS 1362

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom











Specification is subject to change without notice. Errors & Omissions excluded.