

## **Technical Specification**

Product Code: SFBZ553BK

Description: 13A Ingot Fused Connection Unit With Neon & Optional Flex Outlet







## **General Information**

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Dimensions (mm) 86 (W) x 86 (H) x 4 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Screwless Complete

Finish Matt Bronze

Insert Colour Black Compatible Cover Plate SCP153#

> Materials Cover Plate: Stainless Steel Insert: Polycarbonate

> > Rear Housing: Urea Fuse Drawer Cover: Stainless Steel

Neon Lens: Polycarbonate Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Anti Microbial Certified Frequency (Hz) 50 Operating Voltage (AC) 250

Resistive Load Rating (A) 13

> Fuse Fitted Type Plug Top Cartridge Fuse

**Termination Type** Screw

Terminal Size (mm) Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Switched No

Twin Earth Terminals

Neon Indicator Indicator Colour

Product Marking Fused Flex Outlet Available Yes

Flex Outlet Location Front of Plate Flex Outlet Dimension (mm) Ø10

Minimum Back Box Depth (mm) 35

Ingress Protection IP20 Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 1363-4, BS 1362

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com









