Xnightsbridge

DATASHEET



SFR9NLAB

13A 2G DP switched socket with night light function - Antique Brass

www.mlaccessories.co.uk

MLA PART CODE	SFR9NLAB
DESCRIPTION	13A 2G DP switched socket with night light function - Antique Brass
NET WEIGHT (KG)	0.282
FINISH	Antique Brass
INSERT COLOUR	Black
DIMENSIONS (MM)	Height - 87.5 Width - 147.5 Depth - 35.6 Projection - 4.7 Recessed Depth - 26.2
MINIMUM MOUNTING BOX DEPTH	25-35mm (dependent on wiring conditions)
CONSTRUCTION	Construction - 201 Stainless steel
CLASS	I
IP RATING	IP20
WATTAGE (W)	0.8
LAMP TECHNOLOGY	LED
LUMENS (LM)	55
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	73.1
ССТ	4000K
CRI	>85
RUNNING CURRENT (A)	0.01
INPUT VOLTAGE	230V 50Hz
SWITCH TYPE	Double Pole
EARTH TERMINAL	Yes
LOAD/MAX. LOAD	13A
TERMINAL CAPACITY	3 x 2.5mm² or 2 x 4.0mm²
ADDITIONAL FEATURES	Built in Night Light
SENSOR TYPE	Photocell
SENSOR OVERRIDE	No





Xnightsbridge

SENSOR LUX SETTINGS	On 5-15 lux, off 20-40 lux, non-adjustable
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598, BS EN 62493, BS 1363-2
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270850796

Date Created: 05/02/2025 11:40





