

Datasheet

Sloane 2.0



Product Description

A spherical luminaire with an effective light distribution, Sloane 2.0 is ideal for large area amenity applications

Specification Text

The luminaire shall be manufactured from high-pressure Polycarbonate. It shall have an LED efficacy of up to 73.0 lm/W and will be capable of producing up to 4,005 luminaire lumens at 4000K with a CRI >70. It shall have a symmetric optic and is rated at IP65 and IK10.

Specification

Weight: 12.5 - 12.6kg
 Windage: 0.17m²
 Material: Polycarbonate
 Paint finish: RAL7016 Anthracite Grey

Key Features

- 35.0 - 55.0W
- 2,520 - 4,005 Luminaire Lumens
- Efficacy up to 73.0 lm/W
- 4000K, CRI >70
- Lifetime >50,000hr, L70




Mounting Options

- Post Top 76mm

Other Options

- Colour Temperature Option
- Photocell Option
[Contact for details](#)

Optics



Symmetrical

| Code | Power | Luminaire Lumens | Drive Current | Optic | CCT(K) | IP | IK | Weight kg | Paint Finish | Driver Included | Driver Type |
|-----------|-------|------------------|---------------|-------------|--------|------|------|-----------|-------------------------|-----------------|-------------|
| SLOA35F | 35.0 | 2,520 | 700 | Symmetrical | 4000 | IP65 | IK10 | 12.5 | RAL7016 Anthracite Grey | Driver Inc | Fixed |
| SLOA35PEC | 35.0 | 2,520 | 700 | | 4000 | IP65 | IK10 | 12.6 | RAL7016 Anthracite Grey | Driver Inc | Fixed |
| SLOA55F | 55.0 | 4,005 | 1050 | | 4000 | IP65 | IK10 | 12.5 | RAL7016 Anthracite Grey | Driver Inc | Fixed |
| SLOA55PEC | 55.0 | 4,005 | 1050 | | 4000 | IP65 | IK10 | 12.6 | RAL7016 Anthracite Grey | Driver Inc | Fixed |



Dimensions

