


IP66 GREY 16 AMP ELECTRONIC OUTDOOR TIME DELAY SWITCH




- ABS construction
- Multiple accurate time settings using dip switches and rotary adjuster
- Incandescent 16 Amp max, fluorescent 6 Amp max, compact fluorescent 3 Amp max (maximum six fluorescent lights), low voltage 3 Amp max & fans and ventilation equipment 3 Amp max
- Multi point switching, connect two or more units in parallel
- Multi range delay function from 2 seconds to 2 hours: reduces energy consumption
- M.O.M: 1 / O.P.Q: 50

SWITCH SETTING				TIMER FUNCTION
1	2	3	4	
0	0	1	0	2 seconds to 50 seconds
1	0	1	0	50 seconds to 20 minutes
1	1	1	0	20 minutes to 70 minutes
1	1	0	0	70 minutes to 2 hours
-	-	-	1	Timer function disabled

IP20 1440W MAX WHITE ELECTRONIC TIME DELAY PUSH SWITCH



- ABS construction
- Time on adjustable between 12 seconds and 12 minutes
- No neutral connection required: can replace existing switch with no additional wiring
- Max load rating: 6 Amp incandescent 1440W
- Red neon switch perimeter glow light: easy location of switching point
- M.O.M: 5 / O.P.Q: 40




NOT COMPATIBLE WITH LED - SEE PUSHLED BELOW

IP20 WHITE TIME DELAY PUSH SWITCH - LED COMPATIBLE



- Compatible with LED, fluorescent and incandescent loads
- Three load settings - 5-20W, 20-150W, 150-300W
- No neutral connection required: can replace existing switch with no additional wiring
- ABS construction
- Time on adjustable between 12 seconds and 12 minutes
- Red neon switch perimeter glow light
- M.O.M: 1 / O.P.Q: 40

Code
PUSHLED



IP65 GREY WATERPROOF ACCESSORY BOXES

- Maintains IP integrity when cable in use: added safety while load is connected
- Lockable facility (security tag not included): for tamper-proof installation
- Polycarbonate construction: tough, impact & corrosion resistant
- **SSBE** = M.O.M: 5 / O.P.Q: 45
- **TWSBE / DSBE** = M.O.M: 5 / O.P.Q: 20

SSBE


- Accepts standard 1 gang accessory: flexible solution allowing a multitude of different uses

TWSBE

- Accepts standard 2 gang accessory: flexible solution allowing a multitude of different uses

DSBE

- Accepts 2 standard 1 gang accessories: allows a multitude of different configurations



Code	Version
SSBE	1 Gang
TWSBE	2 Gang
DSBE	2 x 1 Gang

DSBE - accessories not included

