

Product Code: SXPF310W

Description: Instant Plaster Filler Light Weight (C3) Cartridge



Benefits

- Ultra lightweight
- Non shrinking
 - Paintable with water based and synthetic paints
 - Sandable after curing
 - Easy to apply
 - Easy to clean
 - Non corrosive towards metals

A non-shrinking, ultra-light, ready mixed filler for filling and repairing cracks and holes in walls and ceilings. It is quick drying and can be over-painted with emulsion based paint 10 - 20 minutes after application, subject to ambient conditions. After curing the product can be sanded.

Colour: White

Applications

For filling joints and screw holes in plasterboard walls and ceilings. For filling and repairing holes and in static joints in concrete, brickwork and plaster.

Directions Of Use

Cut the cartridge seal and screw on the nozzle which should be cut to your required size. Using a skeleton gun, apply the filler into the gap or joint ensuring a good solid fill. Smooth off using a putty knife.

Limitations

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Not suitable for continuous exposure to water
- Not suitable for movement joints

Paintability

Can be over-painted 10 - 20 minutes after application, subject to ambient conditions. Painting over with highly filled emulsion paint can cause craze cracking on the paint surface. Due to the variety of paint compositions, we do recommend preliminary tests for compatibility.

Cleaning

Tools to be cleaned after use with water. Hands can be cleaned with SX Multi-Purpose Cleaning Wipes and/or water and soap.

Additional Information


Application temperature		+5°C to +30°C
Base		Acrylic dispersion
Density		0,57 g/ml
Flow	ISO 7390	<2mm
Frost resistance during transportation		Down to -15°C
Shrinkage		<5%
Skin formation	@ +23°C/50% RH	5 Minutes
Temperature resistance		-20°C to +75°C

These values are typical properties and may vary +/-3%

Shelf Life

In unopened original packaging between + 5°C and +25°C, shelf life till 12 months after production date, stored in a dry place.

Certification

	Emicode EC1 Plus M1 EN 13963: 1A
---	--

Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request.