

TECHNICAL DATA
SMART SYNC CONTROL

WARRANTY
3 years guarantee

PRODUCT CODE
T-8Z-REMOTE



@GAPLightingLtd
GAP Lighting Ltd
/GAPLightingLtd
GAP Lighting Ltd

SMART SYNC



PRODUCT DESCRIPTION


RGB+CCT 8 Zone Touch Controller with smooth dimming function and dynamic multi colour changing programmes. Incorporating wireless RF 2.4G technology. Synchronise multiple products simultaneously or control independently up to 30m range.



SOLAS



iFlood



iFlex

To see all compatible products go to www.gaplighting.co.uk

PRODUCT FEATURES

- RF 2.4G remote control for Smart Sync products
- RGB+CCT - colour wheel and slider bar for manual colour selection
- Brightness control bar | 10 dynamic modes
- Speed control buttons for dynamic modes
- Range up to 30m
- Pair any number of Smart Sync luminaires within 30m range (without obstruction) for synchronised control
- Rechargeable batteries recommended

PRODUCT DATA

Model	T-8Z-REMOTE
Control	8 zone RGB+CCT remote with touch dimming control
Function	Dimming speed variation memory colour saturation dynamic colour changing modes single colour settings master control function
Frequency	2.4GHz high frequency wireless
Remote distance	up to 30 metres
Dimensions	L 152mm W 47mm D 20mm
Material	Plastic housing
Battery	2 x AAA
Approvals	CE ROHS

INSTRUCTIONS FOR USE



Sync: Switch on via the mains switch. Within 3 seconds, select a Zone-ON button and tap 3 times. Pairing is confirmed when the fitting flashes 3 times. If it does not flash, try the procedure again.

Unsync: Switch on via the mains switch. Within 3 seconds, select the Zone-ON button that relates to the zone you wish to unsync and tap 3 times. Unsyncing is confirmed when the fitting flashes 9 times. If it does not flash, try the procedure again.

You can go through the different dynamic modes by pressing 'M' and adjust the speed by pressing 'S+/S-'. Use the 'W' button to select the colour white. Select the saturation control bar to saturate the solid colours when using the colour wheel. Use the brightness level bar to dim.