Xnightsbridge


DATASHEET



TNXTMW

TENAX 230V Wattage and CCT Adjustable LED Gear Tray with Sensor

www.mlaccessories.co.uk



MLA PART CODE	TNXTMW
DESCRIPTION	TENAX 230V Wattage and CCT Adjustable LED Gear Tray with Sensor
NET WEIGHT (KG)	0.261
DIMENSIONS (MM)	Length - 235 Width - 235 Projection - 28
CONSTRUCTION	Construction - Aluminium
CLASS	II
IP RATING	IP20
WATTAGE (W)	10/15/20
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	1360/1480/1405, 1905/2090/1960, 2345/2630/2415
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	151/147/141
CIRCUIT WATTAGE (W)	9.7/14.3/18.6
ССТ	3000/4000/5700K
LIGHT COLOUR	ССТ
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.049/0.067/0.085
DISPLACEMENT FACTOR	>0.7
SVM	0.69
PST-LM	0.36
L70B50 LIFESPAN (HRS)	40,000
DIMMABLE	No
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	230V 50Hz





Xnightsbridge

DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 18W OUTPUT CURRENT - 360mA POWER FACTOR - 0.96 EFFICIENCY FULL LOAD - 0.89 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C
SENSOR TYPE	Microwave
SENSOR OVERRIDE	No
SENSOR DETECTION ANGLE (DEGREES)	150
OPTIMUM DETECTION RANGE (M)	3-5m (mounting height 3m)
SENSOR DURATION	5 seconds - 30 minutes
SENSOR LUX SETTINGS	2 lux - 50 lux / Disable
STANDBY POWER	0.1W
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270876826

Date Created: 08/01/2024 21:21





