



## DATASHEET



### TNXTMWST

### TENAX 230V Wattage and CCT Adjustable Self-test Emergency LED Gear Tray with Sensor

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	TNXTMWST
DESCRIPTION	TENAX 230V Wattage and CCT Adjustable Self-test Emergency LED Gear Tray with Sensor
NET WEIGHT (KG)	0.351
DIMENSIONS (MM)	Length - 235 Width - 235 Projection - 28
CONSTRUCTION	Construction - Aluminium
CLASS	II
IP RATING	IP20
WATTAGE (W)	10/15/20
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	1360/1480/1405, 1905/2090/1960, 2345/2630/2415
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	151/147/141
LUMENS EMERGENCY MODE (LM)	125
CIRCUIT WATTAGE (W)	9.7/14.3/18.6
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.049/0.067/0.085
DISPLACEMENT FACTOR	>0.7
SVM	0.69
PST-LM	0.36
L70B50 LIFESPAN (HRS)	40,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	Yes
OPERATING TEMPERATURE	-5~35°C

INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 18W OUTPUT CURRENT - 360mA POWER FACTOR - 0.96 EFFICIENCY FULL LOAD - 0.89 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 85°C
SENSOR TYPE	Microwave
SENSOR OVERRIDE	No
SENSOR DETECTION ANGLE (DEGREES)	150
OPTIMUM DETECTION RANGE (M)	3-5m (mounting height 3m)
SENSOR DURATION	5 seconds - 30 minutes
SENSOR LUX SETTINGS	2 lux - 50 lux / Disable
BATTERY INCLUDED	Yes
STANDBY POWER	0.1W
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270876857

Date Created: 08/01/2024 21:20

