







VML106

### Switch Disconnector Incomer

#### Characteristics:

- All Design 10 consumer units contain top, bottom & rear knockouts and a meter tail cable entry plate (**VM04CE**) as standard- see page 38 for knockout sizes.
- Supplied with a full metal DIN rail, 100A switch disconnector incomer and a full complement of earth and neutral terminals along with marking labels, busbar and instructions.
- References ending in **SPD** come with a Type 2 SPD fitted.
- Recommended for use with TT systems when utilising RCBO on all outgoing circuits.
- We also recommend the use of cable clamp (**VA10MT**) for use on TT systems, available as an accessory.
- Conforms to BS EN 61439-3 Including Annex ZB (16kA rating).
- For accessories see page 32, for dimensions see page 38, refer to board sizes below.



Description	Size	Cat ref.	Cat ref. With Round Knockouts
2 Way 63A Switch Disconnector Incomer	2	<b>VML202</b>	<b>VML202RK</b>
6 Way 63A Switch Disconnector Incomer	3	<b>VML206</b>	<b>VML206RK</b>
6 Way 100A Switch Disconnector Incomer	3	<b>VML106</b>	<b>VML106RK</b>
10 Way 100A Switch Disconnector Incomer	4	<b>VML110</b>	<b>VML110RK</b>
14 Way 100A Switch Disconnector Incomer	5	<b>VML114</b>	<b>VML114RK</b>
20 Way 100A Switch Disconnector Incomer	7	<b>VML120</b>	<b>VML120RK</b>
8 Way 100A Switch Disconnector Incomer with Factory Fitted <b>Surge Protection</b>	4	<b>VML108SPD</b>	<b>VML108SPDRK</b>
12 Way 100A Switch Disconnector Incomer with Factory Fitted <b>Surge Protection</b>	5	<b>VML112SPD</b>	<b>VML112SPDRK</b>
18 Way 100A Switch Disconnector Incomer with Factory Fitted <b>Surge Protection</b>	7	<b>VML118SPD</b>	<b>VML118SPDRK</b>
6 + 6 Way Dual Row 100A Switch Disconnector Incomer	3 (2)	<b>VML10606</b>	-
10 + 10 Way Dual Row 100A Switch Disconnector Incomer	4 (2)	<b>VML11010</b>	-
14 + 14 Way Dual Row 100A Switch Disconnector Incomer	5 (2)	<b>VML11414</b>	-
20 + 20 Way Dual Row 100A Switch Disconnector Incomer	7 (2)	<b>VML12020</b>	-
8 + 10 Way Dual Row 100A Switch Disconnector Incomer with Factory Fitted <b>Surge Protection</b>	4(2)	<b>VML10810SPD</b>	-
12 + 14 Way Dual Row 100A Switch Disconnector Incomer with Factory Fitted <b>Surge Protection</b>	5(2)	<b>VML11214SPD</b>	-
18 + 20 Way Dual Row 100A Switch Disconnector Incomer with Factory Fitted <b>Surge Protection</b>	7(2)	<b>VML11820SPD</b>	-




VML310AH

### RCCB Incomer

#### Characteristics:

- All Design 10 consumer units contain top, bottom & rear knockouts and a meter tail cable entry plate (**VM04CE**) as standard- see page 38 for knockout sizes.
- Supplied with a full metal DIN rail, 40A, 63A or 100A 30mA Type A RCCB incomer and a full complement of earth and neutral terminals along with marking labels, busbar and instructions.
- Conforms to BS EN 61439-3 Including Annex ZB (16kA rating).
- For accessories see page 32, for dimensions see page 38, refer to board sizes below.



Description	Size	Cat ref.	Cat ref. With Round Knockouts
2 Way 63A 30mA Type A RCCB Incomer	2	<b>VML402AH</b>	-
6 Way 63A 30mA Type A RCCB Incomer	3	<b>VML406AH</b>	-
10 Way 63A 30mA Type A RCCB Incomer	4	<b>VML410AH</b>	-
6 Way 100A 30mA Type A RCCB Incomer	3	<b>VML306AH</b>	<b>VML306AHRK</b>
10 Way 100A 30mA Type A RCCB Incomer	4	<b>VML310AH</b>	<b>VML310AHRK</b>
14 Way 100A 30mA Type A RCCB Incomer	5	<b>VML314AH</b>	<b>VML314AHRK</b>