

## **Technical Specification**

CLICK® ScolmoreGROUP

Product Code: VPBN019BK Description: 10AX 4 Gang 2 Way Plate Switch





## **General Information**

 $\textbf{Dimensions} \hspace{0.5cm} 146\text{mm (W)} \times 88\text{mm (H)} \times 8\text{mm (D)}$ 

**Dimensions With Gasket** 149mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Black Nickel

Insert & Gasket Colour Black

Materials Front Plate: Stainless Steel

Insert & Rocker Switch: Urea Rear Housing: Nylon

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V∼ 50Hz

Load Rating 10AX (Suitable for Inductive Loads)

Plate Fixing Centres 120.6mn
Terminal Size 3.5mmø
Terminal Torque 0.5Nm

**Terminal Capacity** 4 x 1.5mm<sup>2</sup> or 2 x 2.5mm<sup>2</sup>

Two Way Yes
Ingress Protection IP20

Back Box Depth 16mm Minimum

Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

## Additional Information Ensure that the mai

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range.