

## **Technical Specification**



Product Code: VPPN100WH Description: 115V/230V Dual Voltage Shaver Socket Outlet





## **General Information**

Dimensions 88mm (W) x 146mm (H) x 8mm (D)

Dimensions With Gasket 91mm (W) x 149mm (H) x 9mm (D)

Plate Design & Finish Victorian Pearl Nickel

Insert & Gasket Colour White

Materials Front Plate: Stainless Steel

Insert & Rear Housing: Urea

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 240V∼ 50/60Hz

Load Rating 20Va at 230V or 115V

Plate Fixing Centres 120.6mm (Vertical Fixing)

Terminal Size 3.5mmø

Terminal Torque 0.5Nm
Terminal Capacity 2 x 1.5mm² or 1 x 2.5mm²

Twin Earth Terminals Yes

Product Markings Shavers Only, 230V~, 115V~

Fuse PTC Resettable Fuse

Ingress Protection IP21
Back Box Depth 47mm
Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS EN 61558-1:2005+A1:2009

BS EN 61558-2-5:2010

## **Additional Information**

This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms.

PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC

resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com