

Technical Specification



Product Code: VPPN502BK Description: 45A Ingot 2 Gang (Vertica) Double Pole Plate Switch





Representative Image

General Information

88mm (W) x 146mm (H) x 8mm (D) **Dimensions**

Dimensions With Gasket 91mm (W) x 149mm (H) x 9mm (D)

Plate Design & Finish Victorian Pearl Nickel Insert & Gasket Colour Black

Materials Front Plate: Stainless Steel Insert & Rear Housing: Urea

Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V~ 50Hz

Load Rating

Plate Fixing Centres 120.6mm (Vertical Fixing)

Terminal Size 6mmø **Terminal Torque** 2.5Nm **Terminal Capacity** 1 x 16mm² Double Pole Yes

Twin Earth Terminals Yes Ingress Protection

Back Box Depth 35mm Minimum **Operational Temperature** -5°C to +40°C

Warranty 10 Years

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.