

Technical Specification

Product Code: VPPN586BK

Description: 13A Ingot 2 Gang Switched Safety Shutter Socket Outlet With Type A & C USB (4.2A) Outlets



General Information

| | | |
|-----------------------------------|---|--|
| Dimensions | 146mm (W) x 88mm (H) x 8mm (D) | |
| Dimensions With Gasket | 149mm (W) x 91mm (H) x 9mm (D) | |
| Plate Design & Finish | Victorian Pearl Nickel | |
| Insert & Gasket Colour | Black | |
| Materials | Front Plate: Stainless Steel Housing: Nylon Terminals: Brass Contacts: Silver "on-lay" Copper / Brass PCB: Mixed Components | Insert: Urea Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel |
| Maximum Voltage | 250V~ 50Hz | |
| Load Rating | 13A | |
| Plate Fixing Centres | 120.6mm | |
| Terminal Size | 5mmø | |
| Terminal Torque | 1.2Nm | |
| Terminal Capacity | 3 x 2.5mm ² or 2 x 4mm ² | |
| Single Pole | Yes | |
| Twin Earth Terminals | Yes | |
| USB Charging Output Total | 5V DC, 4.2A | |
| Number Of USB Outputs | 2 | |
| USB Type | USB Type "A" & Type "C" | |
| USB Standby Current | 2mA | |
| Product Markings | DC, 5V 3A, 5V 2.4A max, 4.2A | |
| Ingress Protection | IP20 | |
| Back Box Depth | 25mm Minimum | |
| Termination Type | Screw | |
| Operational Temperature | -5°C to +40°C | |
| Warranty | 10 Years, 1 Year Electronics | |
| Standards | BS 1363-2: 2016 +A1: 2018 BS EN 62368-1: 2014 BS EN 62680-1-1: 2015 | |

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Independent Charging: 5V DC, 4.2A – USB Type A (2.4A), USB Type C (3A)
Dual Charging: 5V DC, 4.2A - USB Type A (1.2A), USB Type C (3A)