



660



655



675



024



060



061



100

**Ingot Lockable Sockets**

**655** 13A Ingot 1 Gang DP Key Lockable Socket With Neon

**Lockable Sockets**

**675** 13A 1 Gang DP Key Lockable Socket With Neon

**Lockable Switches**

**660** 20A Double Pole Key Lockable Switch

**Standards:** BS 1363-2, BS EN 60669-1

**Back Box Depth:** 35mm Minimum **Cable Size:** 3 x 2.5mm<sup>2</sup>, 2 x 4mm<sup>2</sup>

**Dimensions:** 1 Gang: (88mm x 88mm x 8mm), 2 Gang: (146mm x 88mm x 8mm)

Understanding the code:

**VP** - Plate Style **BN** - Plate Finish **011** - Product No. **BK** - Insert Colour Please note: AB & BN are only available with black inserts.  
 AB Antique Brass, BR Polished Brass, SB Satin Brass, CH Polished Chrome, SC Satin Chrome,  
 BN Black Nickel, SS Stainless Steel, PN Pearl Nickel, GCBR Georgian Style.

**20A DP Sink/Bath Switch**

**024** 20A DP Sink/Bath Switch With Neon

**Blank Plates**

**060** 1 Gang Blank Plate

**061** 2 Gang Blank Plate

**Standards:** 024: BS EN 60669 100: BS EN 61558

**Back Box Depth:** 024: 25mm min 100: 47mm min. **Cable Size:** 024: 3 x 2.5mm<sup>2</sup> 100: 2 x 1.5mm<sup>2</sup> / 1 x 2.5mm<sup>2</sup>

**Dimensions:** 1 Gang: (88mm x 88mm x 8mm), 2 Gang: (146mm x 88mm x 8mm)

Understanding the code:

**VP** - Plate Style **BN** - Plate Finish **011** - Product No. **BK** - Insert Colour Please note: AB & BN are only available with black inserts.  
 AB Antique Brass, BR Polished Brass, SB Satin Brass, CH Polished Chrome, SC Satin Chrome,  
 BN Black Nickel, SS Stainless Steel, PN Pearl Nickel, GCBR Georgian Style.

**Dual Voltage Shaver Socket**

**100** 115/230V Dual Voltage Shaver Socket

Click® dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5: 2010 making it safe for use in bathrooms.

Shaver outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet.