



Technical Specification

Product Code: VPSS500WH

Description: 45A Ingot 1 Gang Double Pole Plate Switch





Representative Image

General Information	
Dimensions	88mm (W) x 88mm (H) x 8mm (D)
Dimensions With Gasket	91mm (W) x 91mm (H) x 9mm (D)
Plate Design & Finish	Victorian Stainless Steel
Insert & Gasket Colour	White
Materials	Front Plate: Stainless Steel Insert & Rear Housing: Urea Switch Cover: Stainless Steel Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Gasket: Nylon
Maximum Voltage	250V~ 50Hz
Load Rating	45A
Plate Fixing Centres	60.3mm
Terminal Size	6mmø
Terminal Torque	2.5Nm
Terminal Capacity	1 x 16mm ²
Double Pole	Yes
Twin Earth Terminals	Yes
Ingress Protection	IP20
Back Box Depth	35mm Minimum
Operational Temperature	-5°C to +40°C
Warranty	10 Years
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008
Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E**: sales@scolmore.com | **W:** scolmore.com

Page 1 of 1 Rev.1. Errors & Omissions excluded ecification is subject to change without notice