

Technical Specification



Product Code: VPSS504BK Description: 45A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched Socket

Dutlet





Representative Image

General Information

 $\label{eq:definition} \textbf{Dimensions} \qquad 146 \text{mm (W)} \times 88 \text{mm (H)} \times 8 \text{mm (D)}$

Dimensions With Gasket 149mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Stainless Steel

Insert & Gasket Colour Black

Materials Front Plate: Stainless Steel

Insert & Rear Housing: Urea

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V∼ 50Hz

Load Rating 45A
Plate Fixing Centres 120.

e Fixing Centres 120.6mm
Terminal Size 6mmø
Terminal Torque 2.5Nm

Terminal Capacity 1 x 16mm²

Double Pole Yes

Twin Earth Terminals Yes
Ingress Protection IP20

Back Box Depth 35mm Minimum **Operational Temperature** -5°C to +40°C

Warranty 10 Years

Standards BS 4177:1992

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Technical Specification











