

## **Technical Specification**



Product Code: VPSS622BK Description: 20A Double Pole Plate Switch





Representative Image

## **General Information**

Dimensions 88mm (W) x 88mm (H) x 8mm (D)
Dimensions With Gasket 91mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Stainless Steel

Insert & Gasket Colour Black

Materials Front Plate: Stainless Steel

Insert, Switch & Rear Housing: Urea

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V∼ 50Hz

Load Rating 20A

Plate Fixing Centres 60.3mm

Terminal Size 5mmø

Terminal Torque 1.8Nm

Terminal Capacity 4 x 2.5mm²

Double Pole Yes
Twin Earth Terminals Yes
Ingress Protection IP20

Back Box Depth 25mm Minimum

Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

diagram with the relevant product.

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com