




**PERFECT FOR MULTI-PURPOSE  
COMMERCIAL APPLICATIONS**




LED LAMP SPECIFICATIONS:	
Luminaire lumens (with diffuser)	<b>2320 lm</b>
Lumens from chip (no diffuser)	<b>3020 lm</b>
Useful lumens	<b>2200 lm</b>
Rated Wattage	30W
Rated luminous flux	2200 lm
Nominal life time of the lamp	50,000 hrs
Colour temperature	4000K
Number of switching cycles before premature lamp failure	≥15,000
Warm-up time up to 60% of the full light output	Instant Full Light
Dimmable	No
Nominal beam angle	120°
Rated power	30W
Rated lamp lifetime	50,000 hrs
Displacement factor	≥0.9
Lumen maintenance factor at end of nominal life	≥0.8
Starting time	Instant full light
Colour rendering	≥80
Colour consistency	Within a six step Macadam ellipse
Rated peak intensity	478cd
Rated beam angle	120°
Voltage / Frequency	240V~50Hz
Lumen efficacy: 77 lm / W	
This product contains a Light Source of Energy Efficiency Class F	
Not suitable for accent lighting	



### 30W INTEGRATED LED BULKHEAD

- Captive stainless steel screws
  - 20mm knockouts side and rear
  - **WPACKLEDPC:** photocell for dusk to dawn operation
  - Tough polycarbonate housing
  - IK08
  - 5 year warranty
- M.O.M: 1 / O.P.Q: 4



Code	Version	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating
WPACKLED	Standard	Black	30W	4000K	2320 lm	50,000 hrs	IP65
WPACKLEDPC	Photocell						