


DATASHEET



WPCWAEM

230V IP65 2 x Wattage and 3 x CCT Adjustable LED Wall Pack with Photocell Sensor and Emergency

www.mlaccessories.co.uk



MLA PART CODE	WPCWAEM
DESCRIPTION	230V IP65 2 x Wattage and 3 x CCT Adjustable LED Wall Pack with Photocell Sensor and Emergency
NET WEIGHT (KG)	1.2
FINISH	Black
DIFFUSER	Prismatic
DIMENSIONS (MM)	Height - 218 Width - 147 Projection - 74
CONSTRUCTION	Construction - Polycarbonate Construction 2 - & aluminium
CLASS	II
IP RATING	IP65
IK RATING	IK10
WATTAGE (W)	10/15
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1240/1300/1265, 1800/1950/1845
LUMENS LIGHT SOURCE ONLY (LM)	1525/1625/1560, 2160/2370/2190
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	140
LUMENS EMERGENCY MODE (LM)	145
CIRCUIT WATTAGE (W)	15.46
CCT	3000/4000/6500K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.07
SVM	0.008
PST-LM	0.121

LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	No
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
DRIVER	EFFICIENCY FULL LOAD - 92
SENSOR TYPE	Photocell
SENSOR LUX SETTINGS	On <30lx, Off >30lx
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	including battery
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270853308

Date Created: 13/11/2024 13:50

